



# 5th Wheels

## SPECIFICATIONS

• = STANDARD

O = OPTIONAL

N = NOT AVAILABLE

	28' Laredo	31' Monterey	34' Anaheim	34' Pasadena	34' Santa Clara	37' Louisville	37' Memphis	37' Sheridan	40' Atlanta	40' Casper	40' Las Vegas	40' Olympia	40' Tampa	40' Boston	
<b>CHASSIS</b>															
I-BEAM 8" reinforced at axle area with 2x2 structural tubing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
AXLES - Double brake - 5000# rating (6000# rating with radial tire option)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
AXLES - Triple brake - 5000# rating (6000# rating with radial tire option)	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
WHEELS - 15" chrome 6 lug with bullet cover and stainless steel capped wheel nuts and Goodyear whitewall tires - load range D	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
TIRES 16" radial in lieu of std. w/8 bolt chrome wheels (req'd. on 37' models w/slide-out or fiberglass siding) - load range E	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
SHOCK ABSORBERS - two each axle	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
SKID BARS - 1/4" steel plate with internal reinforcement bolted on for easy replacement	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
SKID WHEELS - ball bearing swivel-type with grease zerk bolted on for easy replacement	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
BUMPER - automotive-type primed and painted with rubber insert	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
BUMPER - automotive-type stainless steel with rubber insert	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
JACKS - front leveling - independent electric operation	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
JACKS - rear stabilizer manual operation - set of two bolted to steel chassis	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
POWER LEVELER - A&E Trailer Master with one set Power Twins and one set 5th Wheel Levelers	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
HITCH - 5th wheel assembly for truck bed - crossarm-type - RBW removable bed mount between wheel wells	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
PIN - 5th wheel adjustable either up or down for level towing - RBW	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
PIN STABILIZER BRACE	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
STEP - double fold-up	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
STEP - triple fold-up (required with 16" radial tire option)	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
<b>CONSTRUCTION</b>															
UNDERFLOOR CAVITY completely enclosed, insulated and heated w/easily removed access panels at tanks & slide-out mechanism	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
UNDERBELLY POLYMAX® 1 pc. seamless polyethylene - resists punctures and will not corrode - .030 thick	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
FLOOR FRAMING - 2x4 joists 16" on center w/all joints screwed together w/a total floor/frame thickness of over 12"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
DECKING - 3/4" tongue & groove plywood glued and screwed to joists	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
CARPET LVR & BDR with 3/4" pad - nylon pile, jute backed and treated with Scotch Guard®	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
CARPET throughout with 3/4" pad - nylon pile, jute backed and treated with Scotch Guard®	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
LINOLEUM in kitchen - Congoleum "No-Wax" for easy maintenance (also in Casper bath)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
SIDEWALL & END WALL FRAMING - 2" lumber, 16" O.C. w/screwed joints reinforced at windows & doors	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
END CAPS - 1 piece gel-coated fiberglass, front, rear and under deck	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
SIDING - Yoder side metal treatment resists buckling - .019" aluminum over Fomecor®	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
SIDING - fiberglass - .045" Filon ribbed fiberglass laminated over 1/4" plywood	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
WINDOWS - Hehr with radius corners and tinted glass - all extra large	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
STORM WINDOWS (NA on Egress windows)	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
DOORS with dead bolt and slide bolt locks - screen door has kick panel	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
ROOF FRAMING - 2x4 rafters 16" on center doubled at air conditioner locations	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
ROOF DECKING - 1/4" plywood glued and screwed to roof rafters	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
ROOF - one-piece seamless EPDM rubber roof laminated to the 1/4" plywood	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
INSULATION - Owens Corning fiberglass on roof sections - total construction - R14	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
INSULATION - Styrofoam under fresh and waste water tanks - total construction - R14	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
INSULATION - Owens Corning fiberglass in floor/frame system - total construction - R14	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
INSULATION - Owens Corning fiberglass on sidewalls, fronts and backs - total construction - R7	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
FOMECOR® by Monsanto - walls (except not with fiberglass siding) & floors - a waterproof sheathing & an excellent air infiltration barrier	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<b>PLUMBING</b>															
TANKS - under the floor heated fresh & waste water storage - provides additional above-floor storage space	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
FRESH WATER TANK - 50 gallon	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
FRESH WATER TANKS - dual 50 gallon	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
WASTE HOLDING TANKS - dual 40 gallon (triple 40 gallon on rear kitchen models)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
TANK FLUSHING SYSTEM - santi flush system for holding tanks w/garden hose connection	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
DUMP VALVES located in a convenient exterior trunk area for easy access from the side, not the bottom	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
WATER HEATER - 10 gallon gas/electric with electric re-ignition and by-pass kit	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
WINTERIZING KIT - automatic electric system with electric water heater by-pass and anti-freeze storage tank	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
FAUCET - KITCHEN - single lever with aerator	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
FILTER - water filter system with gooseneck faucet makes your tap water taste spring water fresh	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
PUMP 12-volt demand water system	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
WATER HOOK-UP - direct city pressure water inlet	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
PRE-WIRED & PLUMBED for optional washer/dryer	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
WASHER & DRYER - Kenmore compact stack-type - 2-speed washer w/5 cycles, elec. dryer w/4 cycle & timed stop	N	N	O	O	O	O	O	O	O	O	O	O	O	O	
BRASS hardware in bath	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
TOILET - Thetford Aqua-Magic marine type	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
TUB & SHOWER - 27" x 54" w/one-piece tub surround & folding shower door w/brass trim	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
TUB & SHOWER - 24" x 45" w/one-piece tub surround & folding shower door w/brass trim	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
SHOWER w/one-piece surround and hinged glass door	N	O	N	O	N	O	O	O	N	O	O	O	O	N	
SHOWER HEAD - water saver wall-mounted or hand-held	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<b>LP AND HEATING SYSTEM</b>															
LP BOTTLES - dual 30# (6.7 gal.) steel with regulator (in side compartment)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
LP BOTTLES - dual 40# (8.9 gal.) steel with regulator (in side compartment)	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
LP BOTTLE - 3rd 30# steel bottle in separate compartment under gooseneck	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
LP LEAK DETECTOR for added safety and peace of mind	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
LP REMOTE READ OUT - located on the monitor panel	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
FURNACE Hydro-flame - 30,000 BTU forced air w/electric ignition, remote thermostat, in-floor heat ducts	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
FURNACE Excilber - 35,000 BTU forced air w/electric ignition, remote thermostat, in-floor heat ducts	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
FURNACE Hydro-flame - 40,000 BTU forced air w/electric ignition, remote thermostat, in-floor heat ducts	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
FURNACE second - 35,000 BTU forced air w/electric ignition, remote stat (recommended for cold climates)	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
<b>INTERIOR/EXTERIOR</b>															
SLIDE-OUT - 6 1/2' completely automatic, electric operation with dual power rams and structural support tubes	N	O	O	N	O	O	N	O	N	O	N	N	2-O	O	
SLIDE-OUT - 5 1/2' completely automatic, electric operation with dual power rams and structural support tubes	N	N	N	N	N	N	N	N	N	O	N	N	N	N	
SLIDE-OUT - 8 1/2' completely automatic, electric operation with dual power rams and structural support tubes	N	N	N	N	N	N	O	N	O	N	O	N	O	O	
ROCK SHIELD/TRAVEL AWNING - rear, flush-mounted gel-coated fiberglass with key lock & gas filled struts	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
AWNING - side awning w/tension rafter - extra large to cover all picture window & entry doors A&E 9000 or 8000	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
AWNING BACKING - for individual window openings on street side slide-out, sofa & bedroom windows	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
AWNINGS - for individual windows, helps reduce inside temperature - matches side awning A&E Elite or Deluxe	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
WARDROBE replacing 24" entry door for additional interior storage space (see floor plan options)	N	N	O	N	O	N	O	O	O	O	O	O	N	N	
ROOF RACK AND LADDER	O	O	O	O	O	O	O	O	O	O	O	O	O	O	
TRUNK AREAS - located both on the interior and exterior, provides for a generous amount of storage - w/lights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
GWWR (Gross Vehicle Weight Rating) shown for 15" range D tires - 12,500# GWWR for 16" radial E tires	11200	11300	11400	11450	11400	11500	11500	11500	12500	12500	12500	12500	12500	12500	
HEIGHT - approximate (no A/C) - add 2" for 16" radial tires	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	11'4"	
WIDTH - approximate	95"	95"	95"	95"	95"	95"	95"	95"	95"	95"	95"	95"	95"	95"	
LENGTH - approximate overall	28'10"	31'11"	34'10"	37'11"	34'10"	37'11"	37'11"	37'11"	40'00"	40'00"	40'00"	40'00"	40'00"	40'00"	
PIN HEIGHT - approximate	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	ADJ	