



# Travel Trailers

## SPECIFICATIONS

• = STANDARD      O = OPTIONAL      N = NOT AVAILABLE

	32' Dallas	34' Austin	34' San Antonio	35' St. Paul
<b>CHASSIS</b>				
I-BEAM - 8" reinforced at axle area with 2x2 structural tubing	*	*	*	*
AXLES - Double brake - 5000# rating	*	*	*	*
AXLES - Triple brake - (required with optional slide-out on 34' Models) - 5000# rating	N	O	O	*
WHEELS - 15" chrome, 6-lug w/bullet cover & capped wheel nuts & Goodyear whitewall tires - load range "D"	*	*	*	*
TIRES - 16" radial in lieu of standard with 8-bolt chrome wheels - load range "E" - with 6000# axles	O	O	O	O
SHOCK ABSORBERS - two each axle	*	*	*	*
SKID BARS - 1/4" steel plate with internal reinforcement bolted on for easy replacement	*	*	*	*
SKID WHEELS - ball bearing swivel-type with grease zerk bolted on for easy replacement	O	O	O	O
SKID ROLLER - heavy-duty 3" steel pipe from I-beam to I-beam	O	O	O	O
TONGUE JACK - electrically operated, heavy duty	*	*	*	*
STABILIZER JACKS - front & rear - manual operation - set of four bolted to steel chassis	*	*	*	*
POWER LEVELER - A&E Trailer Master with two sets of A&E Mark V Power Levelers	O	O	O	O
BUMPER - automotive-type, stainless steel with rubber insert	*	*	*	*
<b>CONSTRUCTION</b>				
UNDERFLOOR CAVITY - completely enclosed and insulated w/easily removed access panels at tanks & slide-out mechanism	*	*	*	*
UNDERBELLY Polymax® - 1-piece seamless polyethylene - resists punctures and will not corrode - .030 thick	*	*	*	*
FLOOR FRAMING - 2x4 joists, 16" on center w/all joints screwed together with a total floor/frame thickness of over 12"	*	*	*	*
DECKING - 3/4" tongue and groove plywood - glued and screwed to joists	*	*	*	*
CARPET - Living room and bedroom with 5/8" pad - nylon pile - jute backed	*	*	*	*
CARPET - throughout with 5/8" pad - nylon pile - jute backed	O	O	O	O
LINOLEUM - in kitchen & bath - for easy maintenance	*	*	*	*
SIDEWALL & END WALL FRAMING - 2" lumber - 16" O.C. w/screwed joints reinforced at windows & doors	*	*	*	*
END CAPS - one-piece gel-coated fiberglass, both front & rear	*	*	*	*
SIDING - Yoder side metal treatment resists buckling - .019" aluminum over Fomecor®	*	*	*	*
SIDING - fiberglass - .045" Filon ribbed fiberglass laminated over 1/4" plywood	O	O	O	O
WINDOWS - Hehr with radius corners and tinted glass - all extra large	*	*	*	*
STORM WINDOWS (NA on Egress windows)	O	O	O	O
DOORS with dead bolt and slide bolt locks - screen door has kick panel	*	*	*	*
ROOF FRAMING - 2x4 rafters 16" on center doubled at air conditioner locations	*	*	*	*
ROOF DECKING - 3/8" waterboard glued and screwed to roof rafters	*	*	*	*
ROOF - one-piece seamless EPDM rubber roof laminated to the 3/8" waterboard	*	*	*	*
INSULATION - Owens Corning fiberglass on roof sections - total construction - R14	*	*	*	*
INSULATION - Styrofoam under fresh and waste water tanks - total construction - R14	*	*	*	*
INSULATION - Owens Corning fiberglass in floor/frame system - total construction - R14	*	*	*	*
INSULATION - Owens Corning fiberglass on sidewalls, fronts and backs - total construction - R7	*	*	*	*
ARCTIC INSULATION PACKAGE - R11 insulation front & back. Foam insulation on all tanks. Heat tapes all drain lines & water lines in the floor	O	O	O	O
FOMECOR® by Monsanto - walls (except not with fiberglass siding) & floors - a waterproof sheathing & an excellent air infiltration barrier	*	*	*	*
<b>PLUMBING</b>				
TANKS - under the floor fresh & waste water storage - provides additional above-floor storage space	*	*	*	*
FRESH WATER TANK - 70 gallon	*	*	*	*
WASTE HOLDING TANKS - dual 40 gallon (triple on front kitchen models)	*	*	*	*
TANK FLUSHING SYSTEM - sani flush system for holding tanks w/garden hose connection	O	O	O	O
WATER HEATER - 10 gallon gas/electric with electric re-ignition and by-pass kit	*	*	*	*
WINTERIZING KIT - automatic electric system with electric water heater by-pass and anti-freeze storage tank	O	O	O	O
HEAT PADS - electric - under fresh & waste water tanks - recommended for colder climates	O	O	O	O
SINK - kitchen - porcelain double bowl with two sink covers	*	*	*	*
FAUCET - Kitchen - single lever with aerator	*	*	*	*
FILTER - water filter system with gooseneck faucet makes your tap water taste spring water fresh	O	O	O	O
PUMP - 12-volt demand water system	*	*	*	*
WATER HOOK-UP - direct city pressure water inlet	*	*	*	*
PRE-WIRED & PLUMBED for optional washer/dryer	N	*	N	*
WASHER & DRYER - Kenmore compact stack-type - 2-speed washer w/5 cycles, elec. dryer w/4 cycle & timed stop	N	O	N	O
BRASS hardware in bath	*	*	*	*
HOSE BIBB - under the lav for cleaning the toilet bowl	*	*	*	*
FAUCET - brass single lever lavatory faucet	*	*	*	*
TOILET - Theiford Aqua-Magic marine type	*	*	*	*
TUB & SHOWER - 27" x 54" w/three-piece tub surround & folding shower door w/brass trim	N	N	N	*
TUB & SHOWER - 24" x 45" w/one-piece tub surround & folding shower door w/brass trim	N	N	*	N
TUB & SHOWER - 24" x 36" step-type w/one-piece tub surround & folding shower door w/brass trim	*	*	N	N
SHOWER HEAD - water saver wall-mounted or hand-held	*	*	*	*
<b>LP AND HEATING SYSTEM</b>				
LP BOTTLES - dual 30# (6.7 gal.) steel with automatic change-over regulator & gel-coated fiberglass bottle cover	*	*	*	*
LP BOTTLES - dual 40# (8.9 gal.) steel with automatic change-over regulator & gel-coated fiberglass bottle cover	O	O	O	O
LP LEAK DETECTOR for added safety and peace of mind	O	O	O	O
LP REMOTE READOUT - located on the monitor panel	O	O	O	O
FURNACE Hydro-flame - 30,000 BTU forced air w/electric ignition, remote thermostat, in-floor heat ducts	*	*	*	*
FURNACE Hydro-flame - 40,000 BTU forced air w/electric ignition, remote thermostat, in-floor heat ducts	O	O	O	O
<b>INTERIOR / EXTERIOR</b>				
SLIDE-OUT - 6-1/2' completely automatic, electric operation with dual power rams and structural support tubes	O	O	O	N
SLIDE-OUT - 8-1/2' completely automatic, electric operation with dual power rams and structural support tubes	N	N	N	O
ROCK SHIELD / TRAVEL AWNING - front, flush-mounted gel-coated fiberglass with key lock & gas filled struts	*	*	*	*
ROCK SHIELD / TRAVEL AWNING - rear, flush-mounted gel-coated fiberglass with key lock & gas filled struts	O	O	O	O
AWNING - side awning w/tension rafter - extra large to cover all picture windows & entry doors A&E 9000	O	O	O	O
AWNING BACKING - for individual window awnings on street side on slide-out, sofa, dinette & bedroom windows	*	*	*	*
AWNINGS - for individual windows, helps reduce inside temperature - matches side awning A&E Elite	O	O	O	O
ROOF RACK AND LADDER	O	O	O	O
TRUNK AREAS - located both on the interior and exterior, provides for a generous amount of storage - w/lights	*	*	*	*
GVWR (Gross Vehicle Weight Rating) shown for 15" range "D" tires - 12500# GVWR for 16" radial E tires	10,400	10,650	10,600	12,000
HEIGHT - approximate (no A/C) add 3" for 16" radial tires	9'8"	9'8"	9'8"	9'8"
WIDTH - approximate	9'5"	9'5"	9'5"	9'5"
LENGTH - approximate overall	32'7"	34'11"	34'11"	35'11"
HITCH HEIGHT - approximate - add 3" for 16" radial tires	21"	21"	21"	21"
<b>FURNISHINGS</b>				
VELVET DECOR - woven woods w/curtains in LVR & dinette area w/padded fabric valances trimmed in brass & fabric tie backs	*	*	*	*
DRAPES w/lining & mini blinds in BDR w/ruffled fabric valances & fabric tie backs on tie back brackets	*	*	*	*
MINI BLINDS in bath & galley area w/decorative valances trimmed in brass	*	*	*	*
LINEN DECOR - wooden mini blinds w/curtains in LVR & dinette area w/padded fabric valances & fabric tie backs	O	O	O	O
FLIP LOUNGE with storage below, makes into 42" x 72" bed	*	*	*	*
HIDE-A-BED makes into a queen bed (STD with slide-out models)	O	O	O	O
SWIVEL ROCKER - RV size with bottom skirt and matching fabric arm covers	O	O	O	O
SWIVEL ROCKER - residential size with bottom skirt and arm covers	O	O	O	O
INCLINER swivel rocker - residential size with bottom skirt and arm covers (available with slide-out only)	O	O	O	O