


1995 PRESTIGE VAC-U-BOND WALLS



Roof rack optional.
Ladder standard.
Security lights near all four corners.
Clearance light.
Full fiberglass rear cap with R15 composite insulation value.
Opposing slide-outs create 15' wide LVR (NA on all models).
Fiberglass automotive-style bumper.
.040 aluminum wrap to a fully enclosed underbelly.
One-piece 7/8" thick seamless Weyerhaeuser Structurwood floor has 10-year manufacturer's warranty against delamination and is bonded and screwed to the steel frame.
Two "electric screw" driven slide-out power rams.
12" I-beam main frame.
Two telescoping 2-1/2" slide-out support tubes with roller bearing support.
Fiberglass insulation with 1/4" polystyrene bottom wrap provides R10 composite insulation value.
12" rod and angle crossmembers.
235 BSR 16E tires with 6000-lb. axles, 3500-lb. springs and 2" electric brakes.
30" wide entry door (most models) and lighted exterior assist handle.
Triple fold-a-way steps.
Optional lend-a-hand exterior assist handle. (NA Rear Kitchen triple slide-out models.)
Insulated 2" baggage doors, 23" high, with single key locks and latches for easy access.
.030" high-density polyethylene underbelly.

Full sloping roof for extra interior headroom, with rain gutters and water diverters at all four corners. Composite R25 insulation value.
15,000-BTU air conditioners. (Second A/C optional).
One-piece EPDM rubber roof with 10-year manufacturer's warranty laminated to the 3/8" oriented strandboard.
R19 fiberglass insulation.
6" crowned T-joist-type wood rafters on 16" centers.
Roof fully sheathed with 3/8" oriented strandboard.
Central air conditioning ducts through the roof cavity.
3/16" ply-core sheathing for fabric ceiling.

Smooth 1/4" gel-coated fiberglass exterior walls.
2x2 wood framework at various locations in Prestige sidewalls.
1-1/2" solid core polystyrene insulation - R10 composite wall value.
Interior paneling.

6' ceiling height in bedroom.
Full fiberglass front cap with recessed clearance lights and R15 composite insulation value.
Underdeck storage area (can be outfitted with optional generator).
Full fiberglass underdeck cap.
Adjustable pin box.
Electric front jacks.

TETON'S "PRESTIGE" HAS A THREE-YEAR LIMITED WARRANTY ON THE ULTRASTRUCTURE

Teton Homes® "Prestige" offers its three-year Limited Warranty on the Ultrastructure of a 1995 Teton Fifth Wheel, in addition to 10-year warranties included by other manufacturers on selected items.

This warranty is subject to the individual limitations of the specific suppliers involved, and is subject to their rules and guidelines regarding their products. Teton provides the warranty on the Ultrastructure itself.

Teton Homes® warrants its Ultrastructural framework, a unique blend of wood, steel and polystyrene insulation for 3 years. The Ultrastructure includes the 12" I-beam frame, the sidewalls, and roof structure. If, during

the ownership of the original buyer, any part of the Ultrastructure fails to perform properly because of faulty workmanship by Teton Homes®, it will be replaced without charge for either parts or labor if the proper warranty claim procedures are followed. All other items are covered under the standard Teton® one-year Limited Warranty unless otherwise indicated. See your owner's manual and warranty booklets for further details.

This illustration is representative of Teton® "Prestige" 1995 construction and is not intended to represent any specific model. Due to Teton's continual product improvement, specifications and features are subject to change without prior notification or obligations. Not all options or combination of options are available on all floorplans.