RO S				RO	GR	PR	
	8		Telescoping steel slide support tubes on slide-out in living	S	5	S	Black water tank cleaning system
-			area with roller bearing support	S	S	S	One-piece fiberglass garden tub/shower with corner seat
S	5	S	Single electric screw-driven slide-out power ram on bed-	0	0	0	Garden shower with corner seat to replace garden tub
135000		120	room slide-out-double on XL bedroom slide-out	S	S	S	RV-type tub diverter with water saver hand-held shower wand
S	S	S	Extended adjustable pin box N/A Las Vegas	S	S	S	Decorator glass/brass shower enclosure with towel bar
S	S	N	Heavy-duty Ultra-Fab 5,000 lb. rated independent electric	S	5	S	10-gallon gas/electric direct spark ignition water heater
572.5		Galle Galle	front jack legs	S	S	S	Two 40-gallon gray water holding tanks
N	N	S	Heavy-duty front electric jacks with a single motor	S	S	S	One 40-gallon sewage holding tank
S	S	S	Eight lug painted wheels and spare	S	S	S	One 70-gallon fresh water tank
			CONSTRUCTION	S	S	S	All tanks enclosed within heated floor area
			AN HOLDER CO. CALLANDE STOCKED TO STOCKED THE STOCKED	S	S	S	Polybutylene water lines with copper fittings
S	S	S	Completely enclosed and insulated under floor with R-11	S	S	N	Enclosed low point drains
			fiberglass insulation and 1/4" high-density extruded poly-	S	S	S	Dump valves enclosed with side access dump handles
			styrene board with a composite insulation value of R-25	S	5	N	Porcelain steel lavy basin with overflow
S	S	S	7/8" one-piece seamless oriented strandboard	N	N	S	ABS plastic lavy basin without overflow Single lever brass lavy faucet with pop-up drain
ļ.			"Structurwood" by Weyerhauser on main floor and raised	S	SX	N	
			bath floor with manufacturer's 10-year warranty against delamination	N S		S	Double handle brass lavy faucet with pull-up stopper Washer and dryer prep - n/a on Phoenix
S	S	e	Waterproofing sealant applied to 7/8" oriented strandboard	S	3	S	12-volt demand-type water pump
		3	floor decking for added protection	S	S	N	Water lines between kitchen and bath are heat taped
S	S	S	5/8" CDX plywood gooseneck bedroom flooring	S	S	S	Direct city water hook-up
S	8	S	7" thick roof	S	S	S	3/4" diameter drain for water tank
S	8		Whole-house attic ventilation system that will reduce con-	S	N	N	Sewer hose carrier built into fold-down bumper
(TO)		STO	densation and overheating in the attic	N	S	S	Sewer hose carrier built into frame
S	N	N	Exclusive multi-layered ribbed composite sandwich			8858	
30803		, COM	roof/ceiling assembly providing integral air conditioning			,	LP AND HEATING AND COOLING
			and ventilation cavities and wiring chases - with upper	N	N	S	Dual 30 lb. LP bottles
			and lower layers of 1.5" thick high-density rigid poly-	S	S	0	Dual 40 lb. LP bottles with sight gauges
			styrene board vacuum-pressed to the ceiling and roof sub-	S	S	S	Sliding tray for LP bottles
		-	strates to provide a composite R-25 insulation value	S	S	S	LP pressure-regulator with automatic bottle change-
N	S	S	Plywood roof rafters T-joist-style 16" on center with R-19	- 0			over feature
			fiberglass insulation	S	S	S	Smoke detector
N	S	S	R-19 fiberglass roof insulation providing a composite	S	5	S	LP leak detector
		.0	insulation value of R-25	S	5	S	Two 31,000 BTU/N furnaces on 35', 38' and 40' models
N	8	S	3/8" oriented strandboard "Structurwood" by Weyerhauser	N	S	S	One 35,000 BTU/H furnace on 30' model
			roof recking screwed and glued to roof rafters with manu-	S O	S	S	Zoned heating on 35', 38' and 40' models Storm windows
N		c	facturer's 10-year warranty against delamination Vacubond sidewall construction 2" thick with a core of	S	S	S	15,000 BTU air conditioner–Cool Spot N/A Las Vegas
IN	(III)	0	1.5" expanded high-density rigid polystyrene insulation	S	S	S	13,500 BTU/H ducted basement airconditioner—
			board vacuum-pressed to the one-piece molded smooth	3	13	3	Las Vegas only (heat pump optional)
			gel-coated fiberglass exterior siding and to the interior	0	0	0	Dual 13,500 BTU/H ducted basement air conditioner-
			decorator paneling with a composite R-10 insulation value	~	- 1	×	Las Vegas only (dual heat pumps available)
S	N	N	Vacubond sidewall construction 3" thick with a core of	S	S	S	Solid-state heating and cooling thermostat
1870		550	2.5" thick expanded high-density rigid polystyrene insula-	S	S	S	Prewired for second air conditioner with thermostat
			tion board vacuum- pressed to the one-piece molded			335.52	harness-N/A Las Vegas
			smooth gel-coated fiberglass exterior siding and to the	0	0	0	Second 15,000 BTU/H air conditioner-Cool Spot N/A on
			interior decorator paneling with a composite R-15			100.73	Las Vegas
			insulation value	0	0	0	15,000 BTU/H air conditioner-Cool Spot-with heat pump
		- 1	The latest and the la			100000	replacing standard air conditioner N/A on Las Vegas
			PLUMBING	0	0	0	Second 15,000 BTU/H air conditioner-Cool pot-with
N	N	S	Thetford Starlight toilet			555	heat pump N/A on Las Vegas
S	S	0	Sealand vitreous china toilet w/residential-type seat and lid	S	8	S	Dual air conditioning ducts built into roof and connected
S	8	S	Hand-held toilet spray wand		11		to both air conditioner locations-N/A Las Vegas
S	8	S	Double basin porcelain enameled kitchen sink except	S	8	S	Vained directional air conditioner plastic ceiling registers
			stainless steel in Phoenix				prevents condensation-N/A Las Vegas
S	S	S	Single lever chrome kitchen faucet	S	8	1000000	Ceiling paddle fan-N/A Las Vegas
S	S		Water filter with gooseneck faucet at kitchen sink	S	S	0	Fantastic 12-volt three-speed reversible vent in kitchen
0	0	0.25	Kitchen faucet with pull-out spray faucet head		(E	0	with wall thermostat and rain sensor
S	2	S	Manual winterizing system	S	S	0	Fantastic 12-volt three-speed reversible vent in bathroom
S		S	Manual water heater bypass		line line		with wall thermostat and rain sensor