O GI	R P	R	RO	GR	PI	t e	RO	GR	PR	
S		S Spare tire and wheel on hanger wench	N	S	S	Vacubond sidewall construction 2" thick	S	N	N	Sewer hose carrier built into fold-down
		below floor also provided on Las Vegas			27.	with a core of 1.5" expanded high-density	0000			bumper (N/A on Las Vegas Royal)
7757	1	Royal model				rigid polystyrene insulation board vacu-	N	S	S	Sewer hose carrier built into frame (also
N	1	N Spare tire and wheel on slide-out tray				um-pressed to the one-piece molded				on Las Vegas Royal models)
	ı	behind fold-down bumper N/A on Las				smooth gel-coated fiberglass exterior sid-		ш		
	ı	Vegas Royal model				ing and to the interior decorator paneling		覵		LP AND HEATING AND COOLING
S	1 3	S Skid bars-1/4" steel plate				with a composite R-10 insulation value	S	S	S	Dual 40 lb. LP bottles with sight gauges
S		O Skid roller	S	N	N	Vacubond sidewall construction 3" thick	S	S		Sliding tray for LP bottles
		HWH hydraulic leveling system			133	with a core of 2.5" thick expanded high-	S	S		LP pressure regulator with automatic bot-
0		D Built-in floor safe 9" x 12" x 8" welded to				density rigid polystyrene insulation board		3		tle change-over feature
	9	chassis				vacuum- pressed to the one-piece molded	- 0	0	c	Smoke detector
0		Reese 20,000 lb. swivel hitch for truck				smooth gel-coated fiberglass exterior sid-	S	S		
S		S 10-gauge steel plate generator compart-				ing and to the interior decorator paneling	S	S		LP leak detector
	1	ment floor				with a composite R-15 insulation value	S	S		Two 31,000 BTU/N furnaces except
S		S Two electric screw-driven slide-out power				With a composite IC 15 insulation value				Phoenix model
9	1	rams on living area and XL slide-outs				PLUMBING	N	S	S	One 35,000 BTU/H furnace on 30'
S	Ш,		M	N	c			900		Phoenix model only
S	1	S Telescoping steel slide support tubes on	N	N		Thetford Starlight toilet	S	S	S	Zoned heating except Phoenix model
100	и.	slide-out in living area with roller bearing	S	S	U	Sealand vitreous china toilet w/residential-	S	S		Dual-pane insulated tinted glass windows
		support	200.0			type seat and lid	S	5		GL-20 dark tinted solar-absorbing glass
S	1	S Single electric screw-driven slide-out	S	S	S	Hand-held toilet spray wand	S	S		15,000 BTU air conditioner-Cool Spot
		power ram on bedroom slide-out-double	S	S	S	Double basin porcelain enameled kitchen	0			
		on XL bedroom slide-out				sink except stainless steel in Phoenix and		6		N/A Las Vegas
S		S Extended adjustable pin box N/A Las			ļ.	integrated deep basin Swanstone® sink	S	S		13,500 BTU/H Penguin air conditioner-
	1	Vegas			100	with optional Corian* counters	88	3000		Las Vegas only (heat pump optional)
\$	1	N Heavy-duty Ultra-Fab 5,000 lb. rated inde-	S	S	S	Single lever decorator almond kitchen	S	S	S	Solid-state heating and cooling thermosta
7777	W.	pendent electric front jack legs				faucet		W		controls all the air conditioners and heat
N	1	S Heavy-duty front electric jacks with a sin-	S	S	0	Water filter with decorator almond goose-		Ш		pumps and primary furnace
MIN	1	gle motor				neck faucet at kitchen sink	S	S		Prewired for second air conditioner with
S	9	S Spring-loaded jack leg pins	0	0	0	Single lever almond kitchen faucet with	100			thermostat harness-(Las Vegas is prewired
S		S Eight lug painted wheels and spare				pull-out spray faucet head		ш		for a third roof mounted air conditioner)
m	Ø.	and the parties and spare	S	S	S	Manual winterizing system	0	~		
Ш	B.	CONSTRUCTION	S	S		Manual water heater bypass	U	0		Second 15,000 BTU/H air conditioner-
S		S Completely enclosed and insulated under	S	S		Black water tank cleaning system	100	100		Cool Spot
S	A.	floor with R-11 fiberglass insulation and	S	S		One piece fiberglass neo angle tub/shower	0	O		15,000 BTU/H air conditioner-Cool
7577	II.		0	0	0		- 1	M		Spot-with heat pump replacing standard
	0	1/4" high-density extruded polystyrene				with corner seat (N/A Phoenix, San		m		air conditioner N/A on Las Vegas
		board with a composite insulation value of				Antonio, Casper, Flagstaff and Pasadena	0	0	0	Second 15,000 BTU/H air
	W .	R-25	35.0		-	models)		ш		conditioner-Cool Spot-with heat pump
S	9	8 7/8" one-piece seamless oriented strand-	S	S	S	One-piece fiberglass garden tub/shower	S	S		Dual air conditioning ducts built into roo
80		board "Sturdi-wood" by Weyerhauser on				with corner seat Phoenix, San Antonio,				and connected to both air conditioner
- 88		main floor and raised bath floor with man-			558	Casper, Flagstaff & Pasadena models only	- 4	棚		
100	Ш	ufacturer's 10-year warranty against	0	0	0	Corner shower with corner seat to replace	- 1	w		locations (Connected to all 3 air condi-
100		delamination				tub	-			tioners on the Las Vegas model)
S	1	Waterproofing sealant applied to 7/8" ori-	S	S	S	RV-type tub diverter with brass water saver	S	S		Veined directional air conditioner plastic
Ш	1	ented strandboard floor decking for added				hand-held shower wand				ceiling registers prevents condensation
103	1	protection	S	S	S	Decorator glass/brass shower enclosure	S	S	S	Ceiling paddle fan-N/A Las Vegas
S	9	5 5/8" CDX plywood gooseneck bedroom	S	S		10-gallon gas/electric direct spark ignition	S	5	0	Fantastic 12-volt three-speed reversible
	1	flooring			1	water heater	200			vent in kitchen with wall thermostat and
S		S 7" thick roof	S	S	S	Two 40-gallon gray water holding tanks		ш		rain sensor
S		S Whole-house attic ventilation system that	S	S	S	One 40-gallon sewage holding tank	S	2		Fantastic 12-volt three-speed reversible
		will reduce condensation and overheating	S	S		One 70-gallon fresh water tank				vent in bathroom with wall thermostat an
100	0	in the attic	S	8		All tanks enclosed within heated floor				
100	0,		0	0	2	1. N. 1972 P. 1973 P. 1974 P.	2000			rain sensor
N	I I	N Exclusive multi-layered ribbed composite		4		area	S	S		Three attic ventilators providing convec-
		sandwich roof/ceiling assembly providing	S	S	N	Enclosed low point drains		Ш		tion attic ventilation for moisture and cor
	W.	integral air conditioning and ventilation	S	S	2	Dump valves enclosed with side access	- 4			densation control
	W.	cavities and wiring chases - with upper	.53		45	dump handles	- 1	88		
		and lower layers of 1.5" thick high-density	S	S		Porcelain steel lavy basin with overflow		88		INTERIOR ELECTRICAL
M		rigid polystyrene board vacuum-pressed to	N	N		ABS plastic lavy basin without overflow	S	S	5	12-volt master shut-off switch just inside
1110	8	the ceiling and roof substrates to provide a	S	S	N	Single lever brass lavy faucet with pop-up	~	m		entry door
		composite R-25 insulation value			100	drain	e	c		
S	1	S Plywood roof rafters T-joist-style 16" on	N	N	S	Double handle brass lavy faucet with pull-	S	3	24	12-volt fluorescent ceiling lights through-
1111		center				up stopper	333		250	out
S	1	R-19 fiberglass roof insulation providing a	S	S	S	Washer and dryer prep	S	S	0	12-volt fluorescent ceiling lights in living
		composite insulation value of R-25	S	S		12-volt demand-type water pump				areas
S	1	S 3/8" oriented strandboard "Sturdi-wood"	S			Water lines between kitchen and bath are	S	S	0	12-volt fluorescent ceiling lights in bath-
0	1	by Weyerhauser roof decking screwed and	3		14	heat taped on sloping roof line models	576			room and bedroom
Will.	1	glued to roof rafters with manufacturer's	S	S	C	Direct city water hook-up	S	S		12-volt fluorescent lights under kitchen
1120		10-year warranty against delamination	S	S		3/4" diameter drain for water tank	3			overhead cabinets
200000		THE VEST WOLDSHOV SOSIEST OF STRUBSHOR		00000	S	304 distincter orain for water tank		and the last		OVERHEAD CADINGS